



Deep Sequence Modeling

Ava Soleimany MIT 6.5191 January 19, 2021














Sequences in the Wild




Audio


Sequences in the Wild




Sequence Modeling Applications



One to One
Binary Classification





Many to One
Sentiment Classification




The @MIT Introduction to #DeepLearning is definitely one of the best courses of its kind currently available online

introtodeeplearning.com

12:45 PM - 12 Feb 2018






One to Many Image Captioning



"A baseball player throws a ball."



Many to Many

Machine Translation









Neurons with Recurrence


The Perceptron Revisited



Feed-Forward Networks Revisited




Feed-Forward Networks Revisited



$$x_t \in \mathbb{R}^m$$


$$\hat{y}_t \in \mathbb{R}^n$$

Handling Individual Time Steps






Neurons with Recurrence






Neurons with Recurrence






Recurrent Neural Networks (RNNs)

Recurrent Neural Networks (RNNs)



Apply a recurrence relation at every time step to process a sequence:




Note: the same function and set of parameters are used at every time step

RNNs have a state, h_t , that is updated at each time step as a sequence is processed

RNN Intuition


```
my_{rnn} = RNN()
hidden state = [0, 0, 0, 0]
sentence = ["I", "love", "recurrent", "neural"]
for word in sentence:
    prediction, hidden state = my rnn(word, hidden state)
next_word_prediction = prediction
# >>> "networks!"
```






RNN Intuition


```
my_{rnn} = RNN()
hidden state = [0, 0, 0, 0]
sentence = ["I", "love", "recurrent", "neural"]
for word in sentence:
    prediction, hidden_state = my_rnn(word, hidden_state)
next_word_prediction = prediction
# >>> "networks!"
```




RNN Intuition


```
my_{rnn} = RNN()
hidden state = [0, 0, 0, 0]
sentence = ["I", "love", "recurrent", "neural"]
for word in sentence:
    prediction, hidden state = my rnn(word, hidden state)
next word prediction = prediction
# >>> "networks!"
```







Input Vector x_t




Update Hidden State

$$h_t = \tanh(\boldsymbol{W}_{hh}^T h_{t-1} + \boldsymbol{W}_{xh}^T x_t)$$

Input Vector

 x_t



Output Vector

$$\hat{y}_t = W_{hy}^T h_t$$


Update Hidden State

$$h_t = \tanh(\boldsymbol{W}_{hh}^T h_{t-1} + \boldsymbol{W}_{xh}^T x_t)$$

Input Vector


 x_t

RNNs: Computational Graph Across Time



Represent as computational graph unrolled across time


RNNs: Computational Graph Across Time



RNNs from Scratch



```
class MyRNNCell(tf.keras.layers.Layer):
  def __init__(self, rnn_units, input_dim, output_dim):
    super(MyRNNCell, self).__init__()
    # Initialize weight matrices
    self.W_xh = self.add_weight([rnn_units, input_dim])
    self.W_hh = self.add_weight([rnn_units, rnn_units])
    self.W_hy = self.add_weight([output_dim, rnn_units])
    # Initialize hidden state to zeros
    self.h = tf.zeros([rnn_units, 1])
  def call(self, x):
    # Update the hidden state
    self.h = tf.math.tanh( self.W hh * self.h + self.W xh * x )
    # Compute the output
    output = self.W hy * self.h
    # Return the current output and hidden state
    return output, self.h
```




RNN Implementation in TensorFlow




tf.keras.layers.SimpleRNN(rnn_units)







RNNs for Sequence Modeling




One to One
"Vanilla" NN
Binary classification



Many to One Sentiment Classification



One to Many
Text Generation
Image Captioning



Many to Many
Translation & Forecasting
Music Generation




6.S191 Lab!

... and many other architectures and applications

Sequence Modeling: Design Criteria

To model sequences, we need to:

- I. Handle variable-length sequences
- 2. Track long-term dependencies
- 3. Maintain information about order
- 4. Share parameters across the sequence



Recurrent Neural Networks (RNNs) meet these sequence modeling design criteria

"This morning I took my cat for a walk."

"This morning I took my cat for a walk."
given these words

"This morning I took my cat for a walk."

given these words

predict the next word




"This morning I took my cat for a walk."

given these words


predict the

next word

Representing Language to a Neural Network




Neural networks cannot interpret words




Neural networks require numerical inputs

Encoding Language for a Neural Network




Neural networks cannot interpret words




Neural networks require numerical inputs


Embedding: transform indexes into a vector of fixed size.



I. Vocabulary:
Corpus of words



2. Indexing: Word to index



3. Embedding: Index to fixed-sized vector

Handle Variable Sequence Lengths

The food was great

VS.


We visited a restaurant for lunch

VS.

We were hungry but cleaned the house before eating

Model Long-Term Dependencies

"France is where I grew up, but I now live in Boston. I speak fluent ____."



We need information from **the distant past** to accurately predict the correct word.

Capture Differences in Sequence Order



The food was good, not bad at all.

VS.


The food was bad, not good at all.



Sequence Modeling: Design Criteria

To model sequences, we need to:


- I. Handle variable-length sequences
- 2. Track long-term dependencies
- 3. Maintain information about order
- 4. Share parameters across the sequence



Recurrent Neural Networks (RNNs) meet these sequence modeling design criteria

Backpropagation Through Time (BPTT)


Recall: Backpropagation in Feed Forward Models




Backpropagation algorithm:

- Take the derivative (gradient) of the loss with respect to each parameter
- 2. Shift parameters in order to minimize loss


RNNs: Backpropagation Through Time




RNNs: Backpropagation Through Time



Standard RNN Gradient Flow




Standard RNN Gradient Flow



Computing the gradient wrt h_0 involves many factors of W_{hh} + repeated gradient computation!

Standard RNN Gradient Flow: Exploding Gradients



Computing the gradient wrt h_0 involves many factors of W_{hh} + repeated gradient computation!


Many values > 1:

exploding gradients

Gradient clipping to scale big gradients



Standard RNN Gradient Flow: Vanishing Gradients



Computing the gradient wrt h_0 involves many factors of W_{hh} + repeated gradient computation!

Many values > 1:

exploding gradients

Gradient clipping to scale big gradients

Many values < 1: vanishing gradients

- 1. Activation function
- 2. Weight initialization
- 3. Network architecture



Why are vanishing gradients a problem?



Why are vanishing gradients a problem?

Multiply many small numbers together



Why are vanishing gradients a problem?

Multiply many small numbers together

Errors due to further back time steps have smaller and smaller gradients



Why are vanishing gradients a problem?

Multiply many small numbers together

Errors due to further back time steps have smaller and smaller gradients

Bias parameters to capture short-term dependencies

"The clouds are in the ___"

Why are vanishing gradients a problem?

Multiply many small numbers together

Errors due to further back time steps have smaller and smaller gradients


Bias parameters to capture short-term dependencies

Why are vanishing gradients a problem?

Multiply many small numbers together

Errors due to further back time steps have smaller and smaller gradients

Bias parameters to capture short-term dependencies



Why are vanishing gradients a problem?

Multiply many small numbers together

Errors due to further back time steps have smaller and smaller gradients

Bias parameters to capture short-term dependencies

"The clouds are in the ___"


"I grew up in France, ... and I speak fluent____"

Why are vanishing gradients a problem?

Multiply many small numbers together


Errors due to further back time steps have smaller and smaller gradients

Bias parameters to capture short-term dependencies




"The clouds are in the ___"

"I grew up in France, ... and I speak fluent____"



Trick #1: Activation Functions



Trick #2: Parameter Initialization


Initialize biases to zero

Initialize **weights** to identity matrix
$$I_n = \begin{pmatrix} 1 & 0 & 0 & \cdots & 0 \\ 0 & 1 & 0 & \cdots & 0 \\ 0 & 0 & 1 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \cdots & 1 \end{pmatrix}$$

This helps prevent the weights from shrinking to zero.

Solution #3: Gated Cells

Idea: use a more complex recurrent unit with gates to control what information is passed through




Long Short Term Memory (LSTMs) networks rely on a gated cell to track information throughout many time steps.


Long Short Term Memory (LSTM) Networks

Standard RNN

In a standard RNN, repeating modules contain a simple computation node



LSTM modules contain computational blocks that control information flow




LSTM cells are able to track information throughout many timesteps






Information is added or removed through structures called gates




Gates optionally let information through, for example via a sigmoid neural net layer and pointwise multiplication

How do LSTMs work?


1) Forget 2) Store 3) Update 4) Output




I) Forget 2) Store 3) Update 4) Output LSTMs **forget irrelevant** parts of the previous state



1) Forget **2) Store** 3) Update 4) Output LSTMs **store relevant** new information into the cell state




1) Forget 2) Store **3) Update** 4) Output LSTMs **selectively update** cell state values




1) Forget 2) Store 3) Update 4) Output

The output gate controls what information is sent to the next time step




1) Forget 2) Store 3) Update 4) Output



LSTM Gradient Flow

Uninterrupted gradient flow!




LSTMs: Key Concepts

- 1. Maintain a separate cell state from what is outputted
- 2. Use gates to control the flow of information
 - Forget gate gets rid of irrelevant information
 - Store relevant information from current input
 - Selectively update cell state
 - Output gate returns a filtered version of the cell state
- 3. Backpropagation through time with uninterrupted gradient flow


RNN Applications

Example Task: Music Generation




Input: sheet music

Output: next character in sheet music





Example Task: Sentiment Classification




nput: sequence of words

Output: probability of having positive sentiment

loss = tf.nn.softmax_cross_entropy_with_logits(y, predicted)

Example Task: Sentiment Classification



Tweet sentiment classification





The @MIT Introduction to #DeepLearning is definitely one of the best courses of its kind currently available online introtodeeplearning.com

12:45 PM - 12 Feb 2018







Replying to @Kazuki2048

I wouldn't mind a bit of snow right now. We haven't had any in my bit of the Midlands this winter! :(

2:19 AM - 25 Jan 2019




Potential Issues





Potential Issues chien mange Encoding bottleneck Slow, no parallelization chien eats dog Decoder (French) Encoder (English)

Potential Issues




chien mange Attention mechanisms in neural networks provide learnable memory access eats Encoder (English) Decoder (French)



Application: Trajectory Prediction for Self-Driving Cars




Application: Environmental Modeling



Deep Learning for Sequence Modeling: Summary

- 1. RNNs are well suited for sequence modeling tasks
- 2. Model sequences via a recurrence relation
- 3. Training RNNs with backpropagation through time
- 4. Gated cells like LSTMs let us model long-term dependencies
- 5. Models for music generation, classification, machine translation, and more



6.S191: Introduction to Deep Learning

Lab 1: Introduction to TensorFlow and Music Generation with RNNs

Link to download labs: http://introtodeeplearning.com#schedule

- I. Open the lab in Google Colab
- 2. Start executing code blocks and filling in the #TODOs
 - 3. Need help? Come to the class Gather. Town!